

Serial Position Indicators For Uml-51-Technical Specification

Type	Cat No.	Display type			Display size			Features			Dimensions mm			
		7 Seg	14 Seg	Dot Matrix	1,5	2	No Of Digits	Programmable by the TST	Arrows	Scrolling	H mm	W mm	D mm	Weigh Gr
SSD-2A	EPB-2015	-	-	-	-	+	-	+	+	-	70	55	38	30
SSD-23	EPB-2035	+	-	-	-	+	1	+	-	-	70	115	40	100
SSD-23A	EPB-2035A	+	-	-	-	+	1	+	+	-	70	160	40	130
SSD-24	EPB-2036	+	-	-	-	+	2	+	-	-	70	115	40	140
SSD-24A	EPB-2036A	+	-	-	-	+	2	+	+	-	70	160	40	170
SSD-13	EPB-2040	+	-	-	-	+	2	+	-	-	95	65	35	80
SSD-3	EPB-2045	+	-	-	+	-	1	+	-	-	95	65	35	70
SSD-4	EPB-2046	+	-	-	+	-	2	+	-	-	95	65	35	80

Additional Accessories for UML-51-Technical Specification

Type	Cat. No	Description	Installation remarks	H	W	D	Weigh
SSD-3C	EPB-2045C	Floor card for up & down calls and lift is here	Serial communication	95	65	35	60
SSGN-4	EPB-1107A	2 different direction gong sound-Serial communication	Connected to the SSD	70	70	28	35

Power Supply: 18-20 Vdc.

(+) Available (-)Not Available